

SHADOW MAX



Reg. No. ECP 02007

Graffiti Solutions

www.graffitisolutions.com

1.800.891.0091

G R A F F I T I R E M O V E R

GENERAL DESCRIPTION

SHADOW MAX Graffiti Remover is one of five "Graffiti Max" products, each custom formulated for specific graffiti removal needs.

SHADOW MAX Graffiti Remover is the right choice for the job if you are removing shadows or ghosting from any of the following "porous surfaces."

RECOMMENDED FOR REMOVAL ON

Brick, mortar, masonry, cement, concrete, stucco, Terrazo, pavers, fieldstone, porous tile. Pressure treated or untreated wood.

Natural stone surfaces such as granite, marble, sandstone, porous rocks - both rough or polished.

Porcelain, glazed or ceramic tiles, grout. **Not recommended for use on metal finishes, plexiglass and Lexan.**

PRODUCT FEATURES AND BENEFITS

- **Super penetrating** action for maximum wet out or stubborn shadows and ghosts.
- **Fast removals** - maximum wet out and penetrating action gives MAXIMUM removal speeds.
- **Low odor** with minimal or no ventilation requirement for added safety, indoor or out.
- **Nonflammable**, noncombustible, minimal fire hazard formula.
- **All temperature** effective removals from below freezing cold (24°F) to "very hot (90°F+) conditions.

SAFETY INSTRUCTIONS FOR USE

- **Always wear protective eye wear and chemical resistant gloves. Can cause burns.**
- Protect all exposed skin areas with chemical resistant covering.
- If product gets on skin, wash off immediately. If product gets in eyes, flush with water for 15 minutes.
- Use respirator if sprayed.
- **FOR PROFESSIONAL USE ONLY.**

GENERAL INSTRUCTIONS FOR USE

- Apply by hand trigger sprayer or pump sprayer.
- Allow to penetrate affected area for 15-20 minutes (30-40 minutes in cold temperatures).
- Use power washer with 15° tip with 1000-3000 PSI maximum pressure.
- For optimum performance and speed of removal use hot water (190°F).
- Excellent results may be obtained with a cold water Power Washer with the above specifications by doubling the dwell time (30-40 minutes).
- Repeat process if necessary.
- Clean up all equipment after each use with water.

SPEC'S - GENERAL PROPERTIES

CONSISTENCY

Thin liquid with maximum wetting and penetrating action.

COVERAGE

150 to 300 sq. ft./gal. depending on porosity of surface.

TEMPERATURE USAGE

Not limited, will work slower at cold temperatures.

STORAGE

Stores between 40°F and 130°F. DO NOT FREEZE. If frozen, thaw and remix before using. Keep out of the reach of children.

FLAMMABILITY

Nonflammable, noncombustible. Flash point over 200°F.

V.O.C.S

.4 lbs/gallon, 50 grams/liter.
H.A.P.S. - none.

BIODEGRADABLE

Yes

VOLATILITY

Very low rate of evaporation. Ventilation required in confined areas. Respirator if sprayed.

SHIPPING

Not regulated, D.O.T. Proper shipping name: Cleaning Compound N.O.S., Class 55.

EFFECTIVE ON THE FOLLOWING

Shadows, ghosting or residues that may occur on porous surfaces, after using conventional graffiti removers. These include shadows, ghosts or residues left by spray paint, markers, inks and most other graffiti shadows or ghosts.

TEST FIRST

SHADOW MAX should not be used for any other purpose/removal, without thoroughly testing in an inconspicuous area for effect.

NOTE: Use **ELEPHANT SNOT**® Graffiti Remover **FIRST** for removing graffiti or marks from above surfaces. In most cases, **ELEPHANT SNOT**® will not leave shadows or ghosting, and if they occur, use **SHADOW MAX** to remove.

For removals from all types of metals, "durable" baked on painted surfaces such as auto, bus, truck, other factory applied paints, fiberglass, traffic or reflective signs, use our **SMOOTH MAX** Graffiti Remover.